

polystar

GALAXY COMPACT SINGLE HEAD WEIGHING SYSTEM



GALAXY COMPACT R20-11N

RISCHE + HERFURTH GMBH
Maschinen- und Apparatebau
Kedenburgstraße 53-59
22041 Hamburg

Phone +49 40 65 69 03-0
Fax +49 40 65 61 890
www.polystar-hamburg.de
E-mail: info@polystar-hamburg.de

APPLICATION FIELD

The GALAXY Compact single head weighing system is made of stainless steel and can be used for manual or automatic weighing of coffee beans, granulate, coated tablets, pills, small metal or plastic parts, etc. This unit is simple to operate and to clean. Due to the compact design the GALAXY Compact is especially suitable for operation in small working areas.

GALAXY – Simply weigh precisely!

PARTICULAR ADVANTAGES

- Compact unit made of stainless steel
- Easy to operate, clean and maintain
- Display with 10 product-program memory slots, input via membrane keyboard
- Digital display of fill volumes
- Individually adjustable filling speeds
- Stepless regulation of infeed speed
- Load tray opens by means of pressurised air

OPERATION

Just fill the supply hopper, set the target weight and away you go! There are even two speed settings (coarse and fine dosing) for conveying and dosing your products.

Then, just press the button or actuate the foot pedal to open the scale pan and your bag is filled and ready. And the best bit: The GALAXY Compact learns by itself!

OPTIONAL ACCESSORIES

- Pneumatically dosing flap
- Dust-proof housing with dust extraction system
- Stainless-steel work table
- FLEX touchscreen with up to 99 product program memory slots
- Pneumatical opening of the load tray
- Dosing hopper/adapter (discharge hopper) for smaller quantities
- Data Reporter: Documentation of the individual weighing procedures
- Self-learning weighing technology

TECHNICAL DATA – polystar®

	Galaxy Compact
Capacity	max. ca. 20 weights/minute
Supply hopper	ca. 55 litres
Load tray	ca. 2.5 litres – on request ca. 4 litres
Mains voltage	230 V / 50 cps / 1-phase
Weight	ca. 60.0 kg
Dimensions	ca. 763 x 400 x 1050 mm
Weighing range	20–2000 grams
Vibration chute	130 mm
Compressed air supply	min. 4 bar / max. 6 bar
Consumption	max. 0.1 m ³ / minute
Display	MONO1020 Faber